(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
7 August 2003 (07.08.2003)

PCT

(10) International Publication Number
WO 03/065334 A2

(51) International Patent Classification[7]: G09G 3/00

(21) International Application Number: PCT/JP03/00626

(22) International Filing Date: 24 January 2003 (24.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002-25644 1 February 2002 (01.02.2002) JP
2002-25645 1 February 2002 (01.02.2002) JP

(71) Applicant *(for all designated States except US)*: **PIONEER CORPORATION** [JP/JP]; 4-1, Meguro 1-chome, Meguro-ku, Tokyo 153-8654 (JP).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **OKUDA, Yoshiyuki** [JP/JP]; c/o Corporate Research and Development Laboratory, Pioneer Corporation, 6-1-1, Fujimi, Tsurugashima-shi, Saitama 350-2288 (JP).

(74) Agent: **FUJIMURA, Motohiko**; Fujimura & Associates, Ginza-Ohno Bldg., 1-17, Tsukiji 4-chome, Chuo-ku, Tokyo 104-0045 (JP).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: LIGHT EMITTING CIRCUIT FOR ORGANIC ELECTROLUMINESCENCE ELEMENT AND DISPLAY DEVICE



(57) Abstract: A light emitting circuit and a display device capable of providing refresh action to an organic electroluminescence element to which a diode is connected in series, in a comparatively easy structure, in order to improve the average luminance.

WO 03/065334 A2

ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DESCRIPTION

LIGHT EMITTING CIRCUIT FOR ORGANIC ELECTROLUMINESCENCE ELEMENT AND DISPLAY DEVICE

Technical Field

The present invention relates to a light emitting circuit for an organic electroluminescence element and a display device.

Background Art

An electroluminescence element (hereinafter referred to as 'EL element'), which is a capacitive light emitting element, can be electrically expressed as an equivalent circuit, as shown in Fig. 1. As can be understood from Fig. 1, an element can be substituted by a constitution of a capacity component C and a component E having a diode characteristic coupled in parallel to the capacity component. Therefore, an EL element can be considered to be a capacitive light emitting element. When a light emitting driving DC voltage is applied between the electrodes of the EL element, electric charge is accumulated in the capacity component C. When the voltage across the electrodes exceeds the barrier voltage or the light emission threshold voltage peculiar to the EL element, electric current starts flowing from the electrode (the anode side of the diode component E) to an organic functional layer forming a light emitting layer. As a result, the EL element emits light at light intensity proportional to the current.

The voltage V- current I- luminance L characteristic of the EL element is, as shown in Fig. 2, similar to the characteristic of a diode in that the current I is very small

at a voltage lower than the light emission threshold voltage Vth and increases at a voltage higher than the light emission threshold voltage Vth. Further, the current I and the luminance L are nearly proportional to each other. The EL element shows light emitting luminance proportional to the current I which flows in accordance with a driving voltage V when the driving voltage applied to the EL element exceeds the light emission threshold voltage Vth, and shows no light emitting luminance when the driving voltage V applied to the EL element is equal to or lower than the light emission threshold voltage Vth.

When a voltage is applied to the EL element of which the function has deteriorated for repeated light emission, in a direction contrary to the forward direction, namely, a reverse bias voltage is applied, it is known that there is refresh action such that the function of the EL element is recovered.

As is also still known, in a light emitting circuit for making an EL element emit light, when a driving current is supplied to the EL element through a diode which is connected to the EL element in series, the EL element emits light, and then maintains the light emission by electric charge, which is accumulated in the capacitive component of the EL element in accordance with the driving current, for a while even after stopping the supply of the driving current. This phenomenon is can be effectively used in improving the average luminance of the EL element when a scanning time for every line is short in a display device for displaying through line scanning of a

display panel with a plurality of EL elements arranged in a matrix shape, especially a display panel having a large number of lines.

In a light emitting circuit in which a diode is connected to an EL element in series, however, it is difficult to form a structure for applying a reserve bias voltage to the EL element to provide the refresh action.

Disclosure of Invention

An object of the present invention is to provide a light emitting circuit for an EL element and a display device capable of providing refresh action to the EL element where a diode is connected in series so as to improve the average luminance, in a comparatively easy structure.

According to the present invention, there is provided a light emitting circuit for making an organic electroluminescence element emit light in response to a light emission instruction, comprising: a first diode element connected with the organic electroluminescence element in a same polarity direction in series, a second diode element connected with said organic electroluminescence element at a connection point between said organic electroluminescence element and said first diode element, in a direction contrary to the polarity direction of the first diode element, driving current supplying means for supplying a driving current for light emission in the forward polarity direction to the serial circuit of said organic electroluminescence element and said first diode element in response to the light emission

instruction, and reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said second diode element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

According to the invention, there is provided a display device comprising: a display panel in which a plurality of light emitting cells respectively including organic electroluminescence elements are arranged in a matrix shape; light emitting cell specifying means for specifying a least one light emitting cell to be driven to emit light of said light emitting cells in accordance with input image data; and driving means for making an organic electroluminescence element emit light, said organic electroluminescence element being in the light emitting cell specified by said light emitting cell specifying means, wherein said light emitting cell includes a first diode element connected with said organic electroluminescence element in a same polarity direction in series, and a second diode element connected with said organic electroluminescence element at a connection point between said organic electroluminescence element and said first diode element, in a direction contrary to the polarity direction of the first diode element, and said driving means includes driving current supplying means for supplying a driving current for light emission in the forward polarity direction to the serial circuit of said organic

electroluminescence element and said first diode element in response to the light emission instruction, and reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said second diode element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

According to the present invention, there is provided a light emitting circuit for making an organic electroluminescence element emit light in response to a light emission instruction, comprising: a diode element connected with said organic electroluminescence element in a forward polarity direction in series; a capacitive element connected at the connection point of said organic electroluminescence element and said diode element; driving current supplying means for supplying a driving current in the forward direction to said organic electroluminescence element and said capacitive element through said diode element in response to the light emission instruction; and reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said capacitive element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

According to the present invention, there is provided a light emitting circuit for making an organic

electroluminescence element emit light in response to a light emission instruction, comprising: a diode element connected with said organic electroluminescence element in a forward polarity direction in series; a capacitive element connected with said organic electroluminescence element at the connection point of said organic electroluminescence element and said diode element; first potential application means for applying a first potential, which is higher than a reference potential, to one end of said organic electroluminescence element on a side opposite to the connection point; driving current supplying means for supplying a driving current in the forward direction to said capacitive element through said diode element in response to the light emission instruction; and second potential application means for applying the first potential to one end of said capacitive element on a side opposite to said connection point, after finishing the supply of the driving current by said driving current supplying means.

According to the present invention, there is provided a display device comprising: a display panel in which a plurality of light emitting cells respectively including organic electroluminescence elements are arranged in a matrix shape; light emitting cell specifying means for specifying a least one light emitting cell to be driven to emit light of said light emitting cells in accordance with input image data; and driving means for making an organic electroluminescence element emit light, said organic electroluminescence element

being in the light emitting cell specified by said light emitting cell specifying means, wherein said light emitting cell includes a diode element connected with said organic electroluminescence element in a forward polarity direction in series, and a capacitive element connected at the connection point of said organic electroluminescence element and said diode element, and said driving means includes driving current supplying means for supplying a driving current in the forward direction to said organic electroluminescence element and said capacitive element through said diode element in response to the light emission instruction, and reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said capacitive element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

According to the present invention, there is provided a display device comprising: a display panel in which a plurality of light emitting cells respectively including organic electroluminescence elements are arranged in a matrix shape; light emitting cell specifying means for specifying a least one light emitting cell to be driven to emit light of said light emitting cells in accordance with input image data; and driving means for making an organic electroluminescence element emit light, said organic electroluminescence element being in the light emitting cell specified by said light emitting cell specifying means, said light emitting cell

includes a diode element connected with said organic electroluminescence element in a forward polarity direction in series, and a capacitive element connected with said organic electroluminescence element at the connection point of said organic electroluminescence element and said diode element, and said driving means includes first potential application means for applying a first potential, which is higher than a reference potential, to one end of said organic electroluminescence element on a side opposite to the connection point, driving current supplying means for supplying a driving current in the forward direction to said capacitive element through said diode element in response to the light emission instruction, and second potential application means for applying the first potential to one end of said capacitive element on a side opposite to said connection point, after finishing the supply of the driving current by said driving current supplying means.

Brief Description of Drawings

Fig. 1 shows an equivalent circuit of an EL element.

Fig. 2 schematically shows the driving voltage - current - luminance characteristic of the EL element.

Fig. 3 is a block diagram showing an embodiment of the present invention.

Fig. 4 shows a potential in each operation mode of each point of a light emitting cell of Fig. 3.

Fig. 5 is a block diagram showing another embodiment of the present invention.

Fig. 6 shows a potential in each operation mode of each point of the light emitting cell of Fig. 5.

Fig. 7 is a block diagram showing another embodiment of the present invention.

Fig. 8 shows a potential in each operation mode of each point of the light emitting cell of Fig. 7.

Fig. 9 is a block diagram showing another embodiment of the present invention.

Fig. 10 shows a potential in each operation mode of each point of the light emitting cell of Fig. 9.

Fig. 11 is a block diagram showing another embodiment of the present invention.

Fig. 12 shows a potential in each operation mode of each point of the light emitting cell of Fig. 11.

Detailed Description of the Invention

Hereinafter, embodiments of the present invention will be described in details with reference to the drawings.

Fig. 3 shows the structure of a display device to which the present invention is adopted. The display device comprises a display panel 11, a display controller 12, a scanning reverse bias circuit 13, and a driving current supplying circuit 14.

As illustrated in Fig. 3, the display panel 11 includes driving lines A1 to Am in the vertical direction and scanning lines B1 to Bn in the horizontal direction (line direction) being arranged in a matrix shape, and light emitting cells $20_{1,1}$ to $20_{m,n}$ in the respective intersections formed by the

driving lines A1 to Am and the scanning lines B1 to Bn. The display panel 11 further includes reverse bias lines C1 to Cn in parallel to the respective scanning lines B1 to Bn.

The light emitting cells $20_{1,1}$ to $20_{m,n}$ all consist of the same components. Taking the light emitting cell $20_{1,1}$ as an example, for the sake of explanation, it is provided with an EL element 21 and two diodes 22 and 23. The anode of the diode 22 is connected to the driving line A1 and the cathode thereof is connected to the positive electrode of the EL element 21 and the anode of the diode 23. The negative electrode of the EL element 21 is connected to the scanning line B1 and the cathode of the diode 23 is connected to the reverse bias line C1.

The display controller 12 generates a bias control signal, a driving control signal, and a scanning signal based on an input image data. The scanning signal is a signal for selecting one scanning line in turn, of the scanning lines B1 to Bn during one frame. The driving control signal is a signal for instructing supply of a driving current to at least one of the driving lines A1 to Am, corresponding to the EL element to be made emit light depending on the image data, of the EL elements of m light emitting cells on the one scanning line. The bias control signal is a signal for selecting one reverse bias line of the reverse bias lines C1 to Cn at a timing later than the scanning timing based on the scanning signal and instructing application of a reverse bias voltage to the EL elements of m light emitting cells on the one

reverse bias line. The scanning signal and the bias control signal are supplied to a scanning reverse bias circuit 13 and the driving control signal is supplied to a driving current supplying circuit 14.

The scanning reverse bias circuit 13 includes reverse bias switches 31_1 to 31_n and scanning switches 32_1 to 32_n, which are respectively connected to the reverse bias lines C1 to Cn and the scanning lines B1 to Bn. The reverse bias switches 31_1 to 31_n are provided corresponding to the reverse bias lines C1 to Cn, so as to supply one of a potential Vcc1 and a ground potential (reference potential) selectively to the respective reverse bias lines C1 to Cn, in accordance with the bias control signal. The scanning switches 32_1 to 32_n are provided corresponding to the scanning lines B1 to Bn, so as to supply one of a potential Vcc2 and the ground potential selectively to the respective scanning lines B1 to Bn, in accordance with the scanning signal. Here, Vcc1>Vcc2.

The driving current supplying circuit 14 includes current sources 33_1 to 33_m, which are respectively connected to the driving lines A1 to Am. The current sources 33_1 to 33_m supply a driving current to at least one of the driving lines A1 to Am in accordance with the driving control signal.

In the display device constituted above, the operation in the case of making the EL element 21 of the light emitting cell $20_{1,1}$ emit light by the display controller 12 will be described with reference to Fig. 4. In the description, a potential (potential of the driving line A1) applied to the

anode end of the diode 22 is defined as Pa, a potential (potential of the scanning line B1) applied to the negative electrode of the EL element 21 is defined as Pb, a potential (potential of the reverse bias line C1) applied to the cathode end of the diode 23 is defined as Pc, and a potential applied to the positive electrode of the EL element 21 is defined as Pd, as illustrated in Fig. 3.

In the case of light emission of the EL element 21, there are a scanning mode for scanning the line of the light emitting cells $20_{1,1}$ to $20_{m,1}$, a light emission continuous mode for maintaining light emission of the EL element 21 just after finishing the scan, and a reverse bias application mode for applying a reverse bias voltage to the EL element 21, as operation modes of the light emitting cell $20_{1,1}$, as illustrated in Fig. 4.

In the scanning mode, the reverse bias switch 31_1 and the scanning switch 32_1 each perform a switching operation in accordance with a scanning signal from the display controller 12, the reverse bias switch 31_1 relays the potential Vcc1 to the reverse bias line C1, and the scanning switch 32_1 relays the ground potential to the scanning line B1. Simultaneously with the relay operations, the current source 33_1 supplies the driving current to the driving line A1 in accordance with a driving control signal from the display controller 12.

Namely, since the diode 22 turns on, the driving current from the current source 33_1 flows into the ground through the driving line A1, the diode 22, the EL element 21, the scanning

line B1, and the switch 32_1. The EL element 21 emits light by the flow of the driving current. Further, the driving current charges the capacitive component of the EL element 21.

The potential Pa of the driving line A1 becomes, for example, about 10V, the potential Pb of the scanning line B1 becomes 0V that is the ground potential, the potential Pc of the reverse bias line C1 becomes Vcc1, and the positive electrode potential Pd of the EL element 21 becomes about 7V. Since there is a relationship of Vcc1>Vcc2>7V, the diode 23 is in a reverse bias state, and electric charge is stored into the depletion layer capacitor of the diode 23.

When a scanning time assigned to the scanning line B1 passes, the contents of the scanning signal and the driving control signal from the display controller 12 are changed, the scan of the scanning line B1 is finished, and the selected scanning line is shifted to the scanning line B2. Thus, the light emission continuous mode is started. Since the scanning switch 32_1 performs a switching operation, the potential Vcc2 is relayed to the scanning line B1, and simultaneously, the current source 33_1 stops a supply of the driving current to the driving line A1.

In the light emission continuous mode, the potential Pa of the driving line A1 becomes 0V, the potential Pb of the scanning line B1 becomes Vcc2, and the potential Pc of the reverse bias line C1 remains at Vcc1. Since the capacitive component in the EL element 21 has accumulated charge, and the depletion layer capacitor of the diode 23 also has the

accumulated charge, the accumulated charges flow into the diode component of the EL element 21 as a driving current in the forward direction, so as to maintain the light emission of the EL element 21. Accordingly, the positive electrode potential Pd of the EL element 21 becomes about Vcc2+5V. The EL element 21 stops the light emission when the voltage across the EL element 21 in the forward direction becomes lower than a light emission threshold voltage Vth in accordance with decrease of the accumulated charges.

When a bias control signal from the display controller 12 is generated, the reverse bias application mode is started. In the scanning reverse bias circuit 13, the reverse bias switch 31_1 performs a switching operation in response to the bias control signal so as to supply the ground potential 0V, instead of the potential Vcc1 to the reverse bias line C1. At this time point, since the positive electrode potential Pd of the EL element 21 is a potential level obtained by adding the potential Vcc2 at the potential Pb of the scanning line B1 and the potential of the residual charge of the EL element 21, the diode 23 turns on. By the turning-on of the diode 23, the positive electrode potential Pd is substantially changed to the ground potential 0V. Accordingly, the EL element 21 is in a reverse bias state and is provided with refresh action.

Even when the reverse bias switch 31_1 and the scanning switch 32_1 have performed the switching operation, in accordance with a scanning signal from the display controller 12 for the scan of the scanning line B1, in the scanning mode

where the EL element 21 does not emit light, the current source 33_1 is in an inactive state and does not supply a driving current to the driving line A1. The positive electrode potential Pd at this time becomes about 3V.

Fig. 5 shows another embodiment of the present invention. A display device of Fig. 5 includes a display panel 11, a display controller 12, a scanning reverse bias circuit 13, and a driving current supplying circuit 14, similarly to the display device of Fig. 3. The display panel 11 and the display controller 12 are the same as those of Fig. 3.

The scanning reserve bias circuit 13 includes reverse bias switches 41_1 to 41_n and scanning switches 42_1 to 42_n, which are respectively connected to the reverse bias lines C1 to Cn and the scanning lines B1 to Bn. The reverse bias switches 41_1 to 41_n are provided corresponding to the reverse bias lines C1 to Cn, so as to supply one of a potential Vcc1, a potential Vcc2, and a ground potential selectively to the respective reverse bias lines C1 to Cn in response to a bias control signal. The scanning switches 42_1 to 42_n are provided corresponding to the scanning lines B1 to Bn, so as to supply one of a potential Vcc3 and the ground potential selectively to the respective scanning lines B1 to Bn in accordance with a scanning signal. Here, there are relationships of Vcc1>Vcc2>Vcc3 and Vcc1-Vcc2=Vcc3.

The driving current supplying circuit 14 includes current sources 33_1 to 33_m and switches 43_1 to 43_m, which are respectively connected to the driving lines A1 to Am. The

current sources 33_1 to 33_m supply a driving current to any of the driving lines A1 to Am in accordance with a driving control signal. The switches 43_1 to 43_m are turned on to change the potentials of the driving lines A1 to Am to the ground potential respectively in response to the driving control signal.

In the display device constituted as shown in Fig. 5, the operation in the case where the display controller 12 makes the EL element 21 of the light emitting cell $20_{1,1}$ emit light will be described with reference to Fig. 6. There are a scanning mode for scanning the line of the light emitting cells $20_{1,1}$ to $20_{m,1}$, a light emission continuous mode for maintaining light emission of the EL element 21 just after finishing the scan, and a reverse bias application mode for applying a reverse bias voltage to the EL element 21, as illustrated in Fig. 6.

In the scanning mode, the reverse bias switch 41_1 and the scanning switch 42_1 each perform a switching operation in accordance with a scanning signal from the display controller 12, the reserve bias switch 41_1 relays the potential Vcc2 to the reverse bias line C1, and the scanning switch 42_1 relays the ground potential to the scanning line B1. Simultaneously with these relay operations, in accordance with a driving control signal from the display controller 12, for the light emission of the EL element 21, the current source 33_1 operates to supply a driving current to the driving line A1 and the switch 43_1 is turned off.

Since the diode 22 turns on, the driving current from the current source 33_1 flows into the ground through the driving line A1, the diode 22, the EL element 21, the scanning line B1, and the switch 42_1. This flow of the driving current makes the EL element 21 emit light. The driving current charges the capacitive component of the EL element 21.

The potential Pa of the driving line A1 becomes, for example, about 10V, the potential Pb of the scanning line B1 becomes 0V that is the ground potential, the potential Pc of the reverse bias line C1 becomes Vcc2, and the positive electrode potential Pd of the EL element 21 becomes about 7V. Since there is a relationship of Vcc1>Vcc2>7V, the diode 23 is in a reverse bias state and electric charge is stored into the depletion layer capacitor of the diode 23.

When a scanning time assigned to the scanning line B1 passes, it turns into the light emission continuous mode. In the light emission continuous mode, the contents of the scanning signal and the driving control signal from the display controller 12 are changed, the scan of the scanning line B1 is finished, and the selected scanning line is shifted to the scanning line B2. Thus, the reverse bias switch 41_1 and the scanning switch 42_1 each perform a switching operation. The reverse bias switch 41_1 relays the potential Vcc1 to the reverse bias line C1, and the scanning switch 42_1 relays the potential Vcc3 to the scanning line B1. Simultaneously, the current source 33_1 stops the supply of the driving current to the driving line A1 and the switch 43_1 is turned on,

alternatively, it supplies the driving current to the driving line A1 again, for the light emission of the EL element of the light emitting cell at the intersection of another selected scanning line and the driving line A1 and the switch 43_1 is turned off.

In the light emission continuous mode, when stopping the supply of the driving current to the driving line A1, the potential Pa of the driving line A1 becomes 0V, the potential Pb of the scanning line B1 increases to Vcc3, and the potential Pc of the reverse bias line C1 increases to Vcc1. Since the capacitive component in the EL element 21 has the accumulated charge and the depletion layer capacitor of the diode 23 also has the accumulated charge, the accumulated charges flow into the diode component of the EL element 21 as a driving current in the forward direction, so as to maintain the light emission of the EL element 21. Accordingly, the positive electrode potential Pd of the EL element 21 becomes about Vcc3+7V. The EL element 21 stops the light emission when the voltage across the EL element 21 in the forward direction becomes lower than the light emission threshold voltage Vth (for example, 3V) in accordance with a decrease of the accumulated charges. Thus, the light emission continuous mode is finished.

When the bias control signal from the display controller 12 is generated, the reverse bias application mode is started. In the reverse bias application mode, the reverse bias switch 41_1 in the scanning reverse bias circuit 13 performs a

switching operation in response to the bias control signal from the display controller 12, so as to supply the ground potential 0V instead of the potential Vcc1 to the reverse bias line C1. At this time point, since the positive electrode potential Pd of the EL element 21 is a potential level obtained by adding the potential Vcc3 at the potential Pb of the scanning line B1 and the potential of the residual charge of the EL element 21, the diode 23 turns on. By the turning-on of the diode 23, the positive electrode potential Pd is substantially changed to a voltage Vf (for example, 1V to 2V) which is equal to the on-voltage of the diode 23. Since the positive electrode potential Pd is lower than the potential Vcc3 of the potential Pb, the EL element 21 is in a reverse bias state and is provided with refresh action.

Even when the reverse bias switch 41_1 and the scanning switch 42_1 have performed the switching operation in response to the scanning signal from the display controller 12, for the scan of the scanning line B1, in the scanning mode where the EL element 21 does not emit light, the current source 33_1 is in an inactive state and does not supply a driving current to the driving line A1 and the switch 43_1 is turned on. The positive electrode potential Pd at this time becomes about 3V.

Fig. 7 shows another embodiment of the present invention. A display device in Fig. 7 is designed so that the potential Vcc3 is always applied to the scanning lines B1 to Bn, without having the scanning switches 42_1 to 42_n in the scanning reverse bias circuit 13 shown in Fig. 5. The other structure is the

same as that of the display device of Fig. 5.

In the display device constituted as shown in Fig. 7, the operation in the case where the display controller 12 makes the EL element 21 of the light emitting cell $20_{1,1}$ emit light will be described with reference to Fig. 8.

In the scanning mode, the reverse bias switch 41_1 performs a switching operation in accordance with a scanning signal from the display controller 12 so as to relay the potential Vcc2 to the reverse bias line C1. Simultaneously with the relay operation, in response to a driving control signal from the display controller 12, the current source 33_1 operates to supply a driving current to the driving line A1, for the light emission of the EL element 21, and the switch 43_1 is turned off.

Since the diode 22 turns on, the driving current from the current source 33_1 flows into the power source (not illustrated) of the potential Vcc3 through the driving line A1, the diode 22, the EL element 21, and the scanning line B1. This flow of the driving current makes the EL element 21 emit light. The driving current charges the capacitive component of the EL element 21.

The potential Pa of the driving line A1 becomes, for example, Vcc3+10V, the positive electrode potential Pd of the EL element 21 becomes about Vcc3+7V. Since there is a relationship of Vcc1>Vcc3+7V, the diode 23 is in a reverse bias state and electric charge is stored into the depletion layer capacitor of the diode 23.

When a scanning time assigned to the scanning line B1 passes, the contents of the scanning signal and the driving control signal from the display controller 12 are changed and the selected scanning line is shifted to the scanning line B2 though the potential of the scanning line B1 remains at Vcc3. Thus, the light emission continuous mode is started, and the reverse bias switch 41_1 performs a switching operation to relay the potential Vcc1 to the reverse bias line C1. Simultaneously with the switch operation, the current source 33_1 stops the supply of the driving current to the driving line A1 and the switch 43_1 is turned on, alternatively, it supplies the driving current to the driving line A1, for the light emission of the EL element of the light emitting cell at the intersection of another selected scanning line and the driving line A1 and the switch 43_1 is turned off.

In the light emission continuous mode, the potential Pa of the driving line A1 becomes 0V and the potential Pc of the reverse bias line C1 increases to Vcc1 when stopping the supply of the driving current to the driving line A1. Since the capacitive component in the EL element 21 has the accumulated charge and the depletion layer capacitor of the diode 23 also has the accumulated charge, the accumulated charges flow into the diode component of the EL element 21 as a driving current in the forward direction, so as to maintain the light emission of the EL element 21.

The positive electrode potential Pd of the EL element 21 is increased by $V\gamma=Vcc1\times Cd23/(Cd23+Cell)$ by functioning the

both capacities of the charged capacity Cell of the EL element 21 and the charged capacity Cd23 of the diode 23. The EL element 21 stops the light emission when the voltage in the forward direction of the EL element 21 becomes lower than the light emission threshold voltage Vth (for example, 3V) in accordance with to a decrease of the accumulated charges, thereby finishing the light emission continuous mode.

Assuming that the positive electrode potential Pd at the time of maintaining the light emission of the EL element 21 is $V\gamma=Vcc3+V\alpha$, the positive electrode potential Pd becomes $Vcc3+V\alpha-V\gamma$ when the EL element 21 emits light at a selection of the next scanning line B1. Here, $V\alpha$ is about 7V.

When the bias control signal is generated from the display controller 12, the reverse bias application mode is started. In the reverse bias application mode, similarly to the device of Fig. 5, in the scanning reverse bias circuit 13, the reverse bias switch 41_1 performs the switching operation, according to a bias control signal and supplies the ground potential 0V, instead of the potential Vcc1, to the reverse bias line C1. At this point, since the positive electrode potential Pd of the EL element 21 is the potential level obtained by adding the potential Vcc3 at the potential Pb of the scanning line B1 and the potential of the residual charges, the diode 23 is turned on. By turning on the diode 23, the positive electrode potential Pd is changed to the potential (for example, 1 to 2 V) equal to the on-voltage of the diode 23. Since the positive electrode potential Pd is

lower than Vcc3 at the potential Pb, the EL element 21 is in a reverse bias state and is provided with refresh action.

Even when the reverse bias switch 41_1 has performed the switching operation in accordance with a scanning signal from the display controller 12, for the scan of the scanning line B1, in the scanning mode where the EL element does not emit light, the current source 33_1 is in an inactive and does not supply a driving current to the driving line A1, and the switch 43_1 is turned on. The positive electrode potential Pd of the EL element 21 becomes $Vcc3+V\alpha-V\gamma$. $V\alpha$ is about 3V.

In the above-mentioned respective embodiments, although one light emitting cell is shown per one pixel, three light emitting cells, that are a red light emitting cell, a green light emitting cell and a blue light emitting cell, are formed in one pixel, in a color display matrix typed display panel.

In the above embodiments, it is not necessary to supply a bias control signal from the display control circuit 12 for each scan. For example, the bias control signal may be supplied once every scans by a predetermined number of times.

Fig. 9 shows the structure of a display device to which the present invention is adopted. The display device includes a display panel 11, a display controller 12, a scanning reverse bias circuit 13, and a driving current supplying circuit 14, which are similar to the display device shown in Fig. 3.

As illustrated in Fig. 9, the display panel 11 includes driving lines A1 to Am in the vertical direction and scanning

lines B1 to Bn in the horizontal direction (line direction) being arranged in a matrix shape, and light emitting cells $20_{1,1}$ to $20_{m,n}$ in the respective intersections formed by the driving lines A1 to Am and the scanning lines B1 to Bn. The display panel 11 further includes reverse bias lines C1 to Cn in parallel to the respective scanning lines B1 to Bn.

The light emitting cells $20_{1,1}$ to $20_{m,n}$ all consist of the same components. Taking the light emitting cell $20_{1,1}$ as an example, for the sake of explanation, it is provided with an EL element 21, a diodes 22 and a capacitor 24. The anode of the diode 22 is connected to the driving line A1 and the cathode thereof is connected to the positive electrode of the EL element 21 and one end of the capacitor 24. The negative electrode of the EL element 21 is connected to the scanning line B1 and the other end of the capacitor 24 is connected to the reverse bias line C1.

The display controller 12 generates a bias control signal, a driving control signal, and a scanning signal based on an input image data. The scanning signal is a signal for selecting one scanning line in turn, of the scanning lines B1 to Bn during one frame. The driving control signal is a signal for instructing supply of a driving current to at least one of the driving lines A1 to Am, corresponding to the EL element to be made emit light depending on the image data, of the EL elements of m light emitting cells on the one scanning line. The bias control signal is a signal for selecting one reverse bias line of the reverse bias lines C1 to Cn at a

timing later than the scanning timing based on the scanning signal and instructing application of a reverse bias voltage to the EL elements of m light emitting cells on the one reverse bias line. The scanning signal and the bias control signal are supplied to a scanning reverse bias circuit 13 and the driving control signal is supplied to a driving current supplying circuit 14.

The scanning reverse bias circuit 13 includes reverse bias switches 31_1 to 31_n and scanning switches 32_1 to 32_n, which are respectively connected to the reverse bias lines C1 to Cn and the scanning lines B1 to Bn. The reverse bias switches 31_1 to 31_n are provided corresponding to the reverse bias lines C1 to Cn, so as to supply one of a potential Vcc and a ground potential (reference potential) selectively to the respective reverse bias lines C1 to Cn, in accordance with the bias control signal. The scanning switches 32_1 to 32_n are provided corresponding to the scanning lines B1 to Bn, so as to supply one of the potential Vcc and the ground potential selectively to the respective scanning lines B1 to Bn in accordance with the scanning signal. Here, there is a relationship of Vcc>7V.

The driving current supplying circuit 14 includes current sources 33_1 to 33_m and switches 43_1 to 43_m, which are respectively connected to the driving lines A1 to Am. The current sources 33_1 to 33_m supply a driving current to any of the driving lines A1 to Am in accordance with a driving control signal. The switches 43_1 to 43_m respectively supply the ground potential to the driving lines A1 to Am in

accordance with the driving control signal.

In the display device constituted above, the operation in the case of making the EL element 21 of the light emitting cell $20_{1,1}$ emit light by the display controller 12 will be described with reference to Fig. 10. In the description, a potential (potential of the driving line A1) applied to the anode end of the diode 22 is defined as Pa, a potential (potential of the scanning line B1) applied to the negative electrode of the EL element 21 is defined as Pb, a potential (potential of the reverse bias line C1) applied to the other end of the capacitor 24 is defined as Pc, and a potential applied to the positive electrode of the EL element 21 is defined as Pd, as illustrated in Fig. 9.

In the case of light emission of the EL element 21, there are a scanning mode for scanning the line of the light emitting cells $20_{1,1}$ to $20_{m,1}$, a light emission continuous mode for maintaining light emission of the EL element 21 just after finishing the scan, and a reverse bias application mode for applying a reverse bias voltage to the EL element 21, as operation modes of the light emitting cell $20_{1,1}$, as illustrated in Fig. 10.

In the scanning mode, the reverse bias switch 31_1 and the scanning switch 32_1 each perform a switching operation in accordance with a scanning signal from the display controller 12. The reverse bias switch 31_1 relays the ground potential 0V to the reverse bias line C1, and the scanning switch 32_1 relays the ground potential 0V to the scanning line B1.

Simultaneously with the above relay operations, the current source 33_1 supplies a driving current to the driving line A1 in accordance with a driving control signal from the display controller 12, for the purpose of the light emission of the EL element 21, and the switch 43_1 is turned off.

Since the diode 22 turns on, the driving current from the current source 33_1 flows into the ground through the driving line A1, the diode 22, the EL element 21, the scanning line B1, and the switch 32_1. The EL element 21 emits light by the flow of the driving current. Further, the driving current charges the capacitive component of the EL element 21. Further, part of the driving current from the current source 33_1 flows into the ground through the diode 22, the capacitor 24, and the reverse bias switch 31_1, as a charging current, to charge the capacitor 24.

In the scanning mode, the potential Pa of the driving line A1 becomes, for example, about 10V, the potential Pb of the scanning line B1 and the potential Pc of the reverse bias line C1 become 0V that is the ground potential, and the positive electrode potential Pd of the EL element 21 becomes about 7V.

When a scanning time assigned to the scanning line B1 passes, the light emission continuous mode is started. In the light emission continuous mode, the contents of the scanning signal and the driving control signal from the display controller 12 are changed, the scan of the scanning line B1 is finished, and the selected scanning line is shifted to the

scanning line B2. Thus, the reverse bias switch 31_1 and the scanning switch 32_1 each perform a switching operation. The reverse bias switch 31_1 relays the potential Vcc to the reverse bias line C1, and the scanning switch 32_1 relays the potential Vcc to the scanning line B1. Simultaneously with the switching operations, the current source 33_1 stops the supply of the driving current to the driving line A1 and the switch 43_1 is turned on, alternatively, it supplies a driving current to the driving line A1 for light emission of the EL element of the light emitting cell at the intersection of another selected scanning line and the driving line A1, and the switch 43_1 is turned off.

In the light emission continuous mode, when the supply of the driving current to the driving line A1 is stopped, the potential Pa of the driving line A1 becomes 0V and the diode 22 turns off. The potential Pb of the scanning line B1 and the potential Pc of the reverse bias line C1 increase to Vcc. Since the capacitive component in the EL element 21 has the accumulated charge and the capacitor 24 has the accumulated charges, the accumulated charges flow into the diode component of the EL element 21 as a driving current in the forward direction so as to maintain the light emission of the EL element 21. Accordingly, assuming that the positive electrode potential Pd of the EL element 21 is about Vcc+Vα, Vα=7V. The EL element 21 stops light emission when the voltage across the EL element 21 in the forward direction becomes lower than the light emission threshold voltage Vth (for example, Vα=3V) in

accordance with a decrease of the accumulated charges and the light emission continuous mode is finished.

When a bias control signal from the display controller 12 is generated, the reverse bias application mode is started. In the reverse bias application mode, the reverse bias switch 31_1 in the scanning reverse bias circuit 13 performs a switching operation in response to a bias control signal from the display controller 12 so as to supply the ground potential 0V instead of the potential Vcc to the reverse bias line C1. A change from the potential Vcc to 0V at the other end of the capacitor 24 on the side of the reverse bias line C1 means a change in the potential at the one end on the opposite side of the capacitor 24, namely, the positive electrode potential Pd of the EL element 21. The current source 33_1 stops the supply of the driving current to the driving line A1 and the switch 43_1 is turned on.

Assume that the positive electrode potential Pd of the EL element 21 after the potential change of the reverse bias line C1 is represented by $V\alpha+V\beta$. $V\alpha=3V$ is maintained. Further, assuming that the charged capacity of the EL element 21 is Cell and the charged capacity of the capacitor 24 is C24, $V\beta$ is a voltage obtained by dividing the potential Vcc by two charged capacities Cell and C24, namely $V\beta=Vcc\times Cell/(Cell+C24)$. The forward voltage Vell between the terminals of the EL element 21 becomes $V\alpha+V\beta-Vcc$.

When the potential Vcc is set at a fairly high level and, for example, C24 is set two to four times larger than Cell so

as to satisfy the relationship of C24>Cell, the voltage Vell between the terminals of the EL element 21 becomes lower than 0V. Thus, the EL element 21 is in a reverse bias state and is provided with refresh action.

In the reverse bias application mode, since the residual charges of the capacitor 24 and the EL element 21 remain as they are, the positive electrode potential Pd is maintained. When the reverse bias application mode is finished in accordance with a disappearance of the bias control signal from the display controller 12, the reverse bias switch 31_1 performs a switching operation to relays the potential Vcc to the reverse bias line C1 similarly to the case of the light emission continuous mode. The positive electrode potential Pd of the EL element 21 increases by Vcc and returns into a potential level obtained by adding the potential Vcc at the potential Pb of the scanning line B1 and the potential of the residual charges.

Even when the reverse bias switch 31_1 and the scanning switch 32_1 have performed the switching operation in accordance with a scanning signal from the display controller 12, for the scan of the scanning line B1, in the scanning mode where the EL element 21 does not emit light, the current source 33_1 is in an inactive and the switch 43_1 is in on. Thus, no driving current is supplied to the driving line A1. The positive electrode potential Pd at this time becomes about 3V.

In the above embodiments, it is not necessary to supply a bias control signal from the display controller 12 in every

scan. For example, the bias control signal may be supplied once every scans by a predetermined number of times.

In the above-mentioned embodiments, the driving lines A1 to Am have the ground potential, respectively by the switches 43_1 to 43_m. At the inactive time of each of the current sources 33_1 to 33_m, if the output line thereof becomes the ground potential, the switches 43_1 to 43_m are not necessary.

Fig. 11 shows further another embodiment of the present invention. A display device of Fig. 11 does not includes the scanning switches 32_1 to 32_n in the scanning reverse bias circuit 13 as mentioned in the display device of Fig. 9 and it is designed to always apply the potential Vcc to the scanning lines B1 to Bn. Although a scanning signal is supplied from the display controller 12 to the scanning reverse bias circuit 13, a bias control signal is not supplied. The other structure is the same as that of the display device of Fig. 9. It may be designed to apply the potential Vcc directly to the negative electrode lines of the EL elements of the light emitting cells $20_{1,1}$ to $20_{m,1}$ without passing through the scanning lines B1 to Bn.

In the display device constituted as shown in Fig. 11, the operation in the case where the display controller 12 makes the EL element 21 of the light emitting cell $20_{1,1}$ emit light will be described with reference to Fig. 12.

In the case of light emission of the EL element 21 in Fig. 11, the operation mode of the light emitting cell $20_{1,1}$ includes a scanning mode for scanning the line of the light

emitting cells $20_{1,1}$ to $20_{m,1}$ and a light emitting mode of making the EL element 21 emit light just after finishing the scan, as illustrated in Fig. 12.

In the scanning mode, the reverse bias switch 31_1 performs a switching operation in accordance with a scanning signal from the display controller 12, to relay the potential Vcc to the reverse bias line C1. Simultaneously with the relay operation, the current source 33_1 supplies a driving current to the driving line A1 in accordance with a driving control signal from the display controller 12 to make the EL element 21 emit light and the switch 43_1 is turned off.

Since the diode 22 turns on, the driving current from the current source 33_1 flows into the ground through the driving line A1, the diode 22, the capacitor 24, the reverse bias line C1, and the reverse bias switch 31_1. Namely, the driving current charges the capacitor 24 as a charging current.

When the charging current flows, the negative electrode potential Pb of the EL element 21 is Vcc, while the positive electrode potential Pd is lower than Vcc and about $7V+V\gamma$. Therefore, the EL element 21 is in a reverse bias state and emits no light.

Assuming that the charged capacity of the EL element 21 is defined as Cell and that the charged capacity of the capacitor 24 is defined as C24, $V\gamma=Vcc\times Cell/(Cell+C24)$. $V\beta$ means that the potential Vcc is divided by the two charged capacities Cell and C24. When the potential Vcc is set at a fairly high level and, for example, C24 is set two to four

times larger than Cell so as to satisfy the relation of C24>Cell, the voltage Vell between the terminals of the EL element 21 becomes about 7V+Vγ-Vcc which is lower than 0V. Therefore, the EL element 21 is in a reverse bias state and is provided with refresh action.

When a scanning time assigned to the line of the light emitting cells $20_{1,1}$ to $20_{m,1}$ passes, the contents of the scanning signal and the driving control signal from the display controller 12 are changed, the selected scanning line is shifted to the line of the light emitting cells $20_{1,2}$ to $20_{m,2}$ although the potential Pb remains at Vcc. Thus, the light emitting mode is started, the reverse bias switch 31_1 performs a switching operation to relay the potential Vcc to the reverse bias line C1. Simultaneously with the switching operation, the current source 33_1 stops the supply of the driving current to the driving line A1 and the switch 43_1 is turned on, alternatively, it supplies the driving current to the driving line A1, for the light emission of the EL element of the light emitting cell at the intersection of another selected scanning line and the driving line A1 and the switch 43_1 is turned off.

In the light emitting mode, the potential Pa of the driving line A1 becomes 0V and the potential Pc of the reverse bias line C1 rises up to Vcc when stopping the supply of the driving current to the driving line A1. The positive electrode potential Pd increases by a potential obtained by dividing the changed voltage Vcc of the potential Pc of the

reverse bias line C1 according to the proportion of the two charged capacities Cell and C24, resulting in 7V+Vcc in accordance with a change from V_Y to Vcc. Since the voltage Vell between the terminals of the EL element 12 becomes about 7V, the EL element 21 emits light. When the voltage of the EL element 21 in the forward direction becomes lower than the light emission threshold voltage Vth (for example, 3V) in accordance with a decrease of the accumulated charges, the EL element 21 stops the light emission and the light emitting mode is finished.

Even when the reverse bias switch 31_1 has performed the switching operation in accordance with a scanning signal from the display controller 12, for the purpose of scanning the line of the light emitting cells $20_{1,1}$ to $20_{m,1}$, in the scanning mode where the EL element 21 does not emit light, the current source 33_1 is in an inactive and does not supply a driving current to the driving line A1 and the switch 43_1 is turned on. The positive electrode potential Pd of the EL element 21 becomes about 3V+V_Y and the EL element 21 turns into a reverse bias state. Thereafter, when a scanning time assigned to the line of the light emitting cells $20_{1,1}$ to $20_{m,1}$ passes and the selected scanning line is shifted to the line of the light emitting cells $20_{1,2}$ to $20_{m,2}$, the positive electrode potential Pd becomes 3V+Vcc.

In the above-mentioned respective embodiments, although one light emitting cell per one pixel is shown, three light emitting cells, namely, a red light emitting cell, a green

light emitting cell, and a blue light emitting cell are formed per one pixel in a color display matrix typed display panel.

Further, in the above-mentioned respective embodiments, although the operation of the light emitting cell $20_{1,1}$ has been described, the operations of the other light emitting cells $20_{1,2}$ to $20_{m,n}$ are the same as above.

As mentioned above, according to the present invention, in order to improve the average luminance, refresh action can be provided to the EL element to which a diode is connected in series, in a comparatively easy structure.

Claims

1. A light emitting circuit for making an organic electroluminescence element emit light in response to a light emission instruction, comprising:

a first diode element connected with the organic electroluminescence element in a same polarity direction in series,

a second diode element connected with said organic electroluminescence element at a connection point between said organic electroluminescence element and said first diode element, in a direction contrary to the polarity direction of the first diode element,

driving current supplying means for supplying a driving current for light emission in the forward polarity direction to the serial circuit of said organic electroluminescence element and said first diode element in response to the light emission instruction, and

reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said second diode element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

2. A light emitting circuit according to claim 1, wherein said driving current supplying means includes a current source for supplying the driving current to one end of said first diode element on a side opposite to said connection point for

a predetermined period in response to the light emission instruction, and first switching means for supplying a reference potential to one end of said organic electroluminescence element on a side opposite to said connection point when the driving current is supplied by said current source, and supplying a second potential, which is higher than the reference potential and lower than a first potential, to the one end of said organic electroluminescence element when the driving current is not supplied by said current source, and

said reverse bias application means includes second switching means, after finishing the supply of the driving current by said current source, for supplying the first potential to one end of said second diode element on a side opposite to said connection point, and thereafter, supplying the reference potential to the one end of said second diode element on a side opposite to said connection point during a period when said organic electroluminescence element does not emit light.

3. A light emitting circuit according to claim 1, wherein said driving current supplying means includes a current source for supplying the driving current to one end of said first diode element on a side opposite to said connection point for a predetermined period in response to the light emission instruction, first switching means for supplying a reference potential to one end of said organic electroluminescence element on a side opposite to said connection point when the

driving current is supplied by said current source, and supplying a third potential, which is higher than the reference potential, to the one end of said organic electroluminescence element when the driving current is not supplied by said current source, and a switch for supplying the reference potential to one end of said first diode element on a side opposite to said connection point when the driving current is not supplied by said current source, and

said reverse bias application means includes second switching means for supplying a second potential, which is higher than the third potential, to one end of said second diode element on a side opposite to said connection point when the driving current is supplied by said current source, after finishing the supply of the driving current by said current source, supplying a first potential, which is higher than the second potential, to the one end of said second diode element, and thereafter, supplying the reference potential to the one end of said second diode element.

4. A light emitting circuit according to claim 1, wherein said driving current supplying means includes a current source for supplying the driving current to one end of said first diode element on a side opposite to the connection point for a predetermined period in response to the light emission instruction, means for supplying a third potential, which is higher than a reference potential, to one end of said organic electroluminescence element on a side opposite to said connection point, and a switch for supplying the reference

potential to one end of said first diode element on a side opposite to the connection point when the driving current is not supplied by said current source, and

said reverse bias application means includes second switching means for supplying a second potential, which is higher than the third potential, to one end of said second diode element on a side opposite to said connection point when the driving current is supplied by said current source, after finishing the supply of the driving current by said current source, supplying a first potential, which is higher than the second potential, to the one end of said second diode element, and thereafter, supplying the reference potential to the one end of said second diode element.

5. A display device comprising:

a display panel in which a plurality of light emitting cells respectively including organic electroluminescence elements are arranged in a matrix shape;

light emitting cell specifying means for specifying a least one light emitting cell to be driven to emit light of said light emitting cells in accordance with input image data; and

driving means for making an organic electroluminescence element emit light, said organic electroluminescence element being in the light emitting cell specified by said light emitting cell specifying means,

wherein said light emitting cell includes a first diode element connected with said organic electroluminescence

element in a same polarity direction in series, and

a second diode element connected with said organic electroluminescence element at a connection point between said organic electroluminescence element and said first diode element, in a direction contrary to the polarity direction of the first diode element, and

said driving means includes driving current supplying means for supplying a driving current for light emission in the forward polarity direction to the serial circuit of said organic electroluminescence element and said first diode element in response to the light emission instruction, and

reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said second diode element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

6. A display device according to claim 5, wherein said light emitting cell specifying means specifies said light emitting cell to be driven emit light by sequentially scanning a plurality of lines of said display panel.

7. A light emitting circuit for making an organic electroluminescence element emit light in response to a light emission instruction, comprising:

a diode element connected with said organic electroluminescence element in a forward polarity direction in series;

a capacitive element connected at the connection point of said organic electroluminescence element and said diode element;

driving current supplying means for supplying a driving current in the forward direction to said organic electroluminescence element and said capacitive element through said diode element in response to the light emission instruction; and

reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said capacitive element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

8. A light emitting circuit according to claim 7, further comprising light emission maintaining means for maintaining a potential difference between both ends of the serial circuit of said organic electroluminescence element and said capacitive element substantially at zero after finishing the supply of the driving current by said driving current supplying means.

9. A light emitting circuit according to claim 7, wherein said driving current supplying means includes a current source for supplying the driving current to one end of said diode element on a side opposite to said connection point for a predetermined period in response to the light emission instruction, and first switching means for supplying a

reference potential to one end of said organic electroluminescence element on a side opposite to the connection point when the driving current is supplied by said current source, and supplying a first potential, which is higher than the reference potential, to the one end of said organic electroluminescence element when the driving current is not supplied by said current source, and

said reverse bias application means includes second switching means, after finishing the supply of the driving current by said current source, for supplying the first potential to one end of said capacitive element on a side opposite to said connection point, and thereafter, supplying the reference potential to the one end of said capacitive element during a period when said organic electroluminescence element does not emit light.

10. A light emitting circuit for making an organic electroluminescence element emit light in response to a light emission instruction, comprising:

a diode element connected with said organic electroluminescence element in a forward polarity direction in series;

a capacitive element connected with said organic electroluminescence element at the connection point of said organic electroluminescence element and said diode element;

first potential application means for applying a first potential, which is higher than a reference potential, to one end of said organic electroluminescence element on a side

opposite to the connection point;

driving current supplying means for supplying a driving current in the forward direction to said capacitive element through said diode element in response to the light emission instruction; and

second potential application means for applying the first potential to one end of said capacitive element on a side opposite to said connection point, after finishing the supply of the driving current by said driving current supplying means.

11. A display device comprising:

a display panel in which a plurality of light emitting cells respectively including organic electroluminescence elements are arranged in a matrix shape;

light emitting cell specifying means for specifying a least one light emitting cell to be driven to emit light of said light emitting cells in accordance with input image data; and

driving means for making an organic electroluminescence element emit light, said organic electroluminescence element being in the light emitting cell specified by said light emitting cell specifying means,

wherein said light emitting cell includes a diode element connected with said organic electroluminescence element in a forward polarity direction in series, and

a capacitive element connected at the connection point of said organic electroluminescence element and said diode

element, and

said driving means includes driving current supplying means for supplying a driving current in the forward direction to said organic electroluminescence element and said capacitive element through said diode element in response to the light emission instruction, and

reverse bias application means for applying a voltage to the serial circuit of said organic electroluminescence element and said capacitive element in the direction contrary to the forward polarity direction of said organic electroluminescence element when said organic electroluminescence element does not emit light.

12. A display device according to claim 11, wherein said light emitting cell specifying means specifies a light emitting cell to be driven emit light by seguentially scanning a plurality of lines of said display panel.

13. A display device comprising:

a display panel in which a plurality of light emitting cells respectively including organic electroluminescence elements are arranged in a matrix shape;

light emitting cell specifying means for specifying a least one light emitting cell to be driven to emit light of said light emitting cells in accordance with input image data; and

driving means for making an organic electroluminescence element emit light, said organic electroluminescence element being in the light emitting cell specified by said light

emitting cell specifying means,

said light emitting cell includes a diode element connected with said organic electroluminescence element in a forward polarity direction in series, and

a capacitive element connected with said organic electroluminescence element at the connection point of said organic electroluminescence element and said diode element, and

said driving means includes first potential application means for applying a first potential, which is higher than a reference potential, to one end of said organic electroluminescence element on a side opposite to the connection point,

driving current supplying means for supplying a driving current in the forward direction to said capacitive element through said diode element in response to the light emission instruction, and

second potential application means for applying the first potential to one end of said capacitive element on a side opposite to said connection point, after finishing the supply of the driving current by said driving current supplying means.

14. A display device according to claim 11, wherein said light emitting cell specifying means specifies a light emitting cell to be driven emit light by sequentially scanning a plurality of lines of said display panel.

FIG. 1



FIG. 2



FIG. 3


IMAGE DATA
12
14
DISPLAY CONTROLLER
DRIVING CONTROL SIGNAL
SCANNING SIGNAL
BIAS CONTROL SIGNAL
33_1
33_2
33_m
$20_{1,1}$
$20_{2,1}$
$20_{m,1}$
A1
A2
Am
Pa
Pb
Pc
Pd
22
23
21
Vcc1
Vcc2
C1
C2
Cn
B1
B2
Bn
31_1
31_2
31_n
32_1
32_2
32_n
$20_{1,2}$
$20_{2,2}$
$20_{m,2}$
$20_{1,n}$
$20_{2,n}$
$20_{m,n}$
13
11

FIG. 4

OPERATING MODE		POTENTIAL Pa	POTENTIAL Pb	POTENTIAL Pc	POTENTIAL Pd
SCANNING MODE	LIGHT EMISSION	ABOUT 10V	0V	Vcc1	ABOUT 7V
	NON-LIGHT EMISSION	0V	0V	Vcc1	ABOUT 3V
LIGHT EMISSION CONTINUOUS MODE		0V	Vcc2	Vcc1	Vcc2 + 5V
REVERSE BIAS APPLICATION MODE		0V	Vcc2	0V	0V

FIG. 5


12
IMAGE DATA
DISPLAY CONTROLLER
DRIVING CONTROL SIGNAL
14
SCANNING SIGNAL
BIAS CONTROL SIGNAL
13
11
A1
A2
Am
Pa
Pb
Pc
Pd
C1
C2
Cn
B1
B2
Bn
Vcc1
Vcc2
Vcc3
22
23
21

FIG. 6

OPERATING MODE		OPERATING STATE	POTENTIAL Pa	POTENTIAL Pb	POTENTIAL Pc	POTENTIAL Pd
SCANNING MODE	LIGHT EMISSION	CURRENT SOURCE 33_1: ACTIVE SWITCH 43_1: OFF	10V	0V	Vcc2	ABOUT 7V
	NON-LIGHT EMISSION	CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	0V	Vcc2	ABOUT 3V
LIGHT EMISSION CONTINUOUS MODE		STATE CORRESPONDING TO ANOTHER SCANNING LINE	0V	Vcc3	Vcc1	Vcc3 + 5V
REVERSE BIAS APPLICATION MODE		CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	Vcc3	0V	Vf

FIG. 7


12
IMAGE DATA
DISPLAY CONTROLLER
DRIVING CONTROL SIGNAL
14
SCANNING SIGNAL
BIAS CONTROL SIGNAL
13
11
A1
A2
Am
Pa
Pb
Pc
Pd
Vcc1
Vcc2
Vcc3
C1
C2
Cn
B1
B2
Bn
22
23
21

FIG. 8

OPERATING MODE		OPERATING STATE	POTENTIAL Pa	POTENTIAL Pb	POTENTIAL Pc	POTENTIAL Pd
SCANNING MODE	LIGHT EMISSION	CURRENT SOURCE 33_1: ACTIVE SWITCH 43_1: OFF	ABOUT 10V	Vcc3	Vcc2	$Vcc3 + V\alpha - V\gamma$ ($V\alpha = 7V$)
	NON-LIGHT EMISSION	CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	Vcc3	Vcc2	$Vcc3 + V\alpha - V\gamma$ ($V\alpha = 3V$)
LIGHT EMISSION CONTINUOUS MODE		STATE CORRESPONDING TO ANOTHER SCANNING LINE	0V	Vcc3	Vcc1	$Vcc3 + V\alpha$
REVERSE BIAS APPLICATION MODE		CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	Vcc3	0V	Vf

FIG. 9


12
IMAGE DATA
DISPLAY CONTROLLER
DRIVING CONTROL SIGNAL
14
SCANNING SIGNAL
BIAS CONTROL SIGNAL
13
11
A1
A2
Am
Pa
Pb
Pc
Pd
C1
C2
Cn
B1
B2
Bn
Vcc
22
24
21

FIG. 10

OPERATING MODE		OPERATING STATE	POTENTIAL Pa	POTENTIAL Pb	POTENTIAL Pc	POTENTIAL Pd
SCANNING MODE	LIGHT EMISSION	CURRENT SOURCE 33_1: ACTIVE SWITCH 43_1: OFF	ABOUT 10V	0V	0V	ABOUT 7V
	NON-LIGHT EMISSION	CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	0V	0V	ABOUT 3V
LIGHT EMISSION CONTINUOUS MODE		STATE CORRESPONDING TO ANOTHER SCANNING LINE	0V	Vcc	Vcc	Vcc + Vα
REVERSE BIAS APPLICATION MODE		CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	Vcc	0V	Vcc + Vβ

FIG. 11


IMAGE DATA
12
DISPLAY CONTROLLER
DRIVING CONTROL SIGNAL
SCANNING SIGNAL
14
33_1
33_2
33_m
43_1
43_2
43_m
$20_{1,1}$
$20_{2,1}$
$20_{m,1}$
$20_{1,2}$
$20_{2,2}$
$20_{m,2}$
$20_{1,n}$
$20_{2,n}$
$20_{m,n}$
A1
A2
Am
Pa
Pb
Pc
Pd
22
24
21
Vcc
31_1
31_2
31_n
C1
C2
Cn
B1
B2
Bn
13
11

FIG. 12

OPERATING MODE		OPERATING STATE	POTENTIAL Pa	POTENTIAL Pb	POTENTIAL Pc	POTENTIAL Pd
SCANNING MODE	LIGHT EMISSION	CURRENT SOURCE 33_1: ACTIVE SWITCH 43_1: OFF	ABOUT 10V	Vcc	0V	ABOUT 7V + Vcc
	NON-LIGHT EMISSION	CURRENT SOURCE 33_1: INACTIVE SWITCH 43_1: ON	0V	Vcc	0V	ABOUT 3V + Vcc
LIGHT EMITTING MODE	LIGHT EMISSION	STATE CORRESPONDING TO ANOTHER SCANNING LINE	0V	Vcc	Vcc	7V + Vcc ~ 3V + Vcc
	NON-LIGHT EMISSION		0V	Vcc	0V	3V + Vcc

HPS Trailer Page
for

Walk-Up_Printing

UserID: rp

Printer: knx_10c20_gbwqptr

Summary

Document	Pages	Printed	Missed	Copies
WO003065334	58	58	0	1
Total (1)	58	58	0	-